FORM KNURLING TOOL F711













ADDED VALUES

- All common knurl profiles can be produced
- Single plus double roller system for maximum flexibility
- Firmly defined centre height
- Adjustment of alignment is possible

Order no.	Model	Workpiece Ø [mm]	Knurling wheel (Ø x w x b) [mm]	Dimensions [mm]						
				а	b	С	d	е	f	Х
32000226	F711-10R	2.5 – 24	10 x 4 x 4	10	10	101.5	16.5	21.5	24	2
32000223	F711-12R	2.5 – 24	10 x 4 x 4	12	12	101.5	16.5	21.5	24	2
32000217	F711-20U	7 – 120	20 x 8 x 6	20	20	104.5	20	24.5	40.4	2.5
32000218	F711-25U	7 – 120	20 x 8 x 6	25	20	104.5	20	24.5	45.2	2.5

Left-hand version of shank dimensions 10 and 12 mm available on request.

For the single-wheel use of this tool (shank size 10 or 12 mm) you may insert a knurling wheel measuring 15 x 4 x 4 mm. The maximum workpiece \emptyset is then extended to 50 mm.

SPARE PART

Order no.	Knurling wheel (Ø x w x b) [mm]				
06TER1036	10 x 4 x 4				
06TER0965	20 x 8 x 6				









